



Address: Erbil, Southern Industry

TEL: +964 770 445 4256

E-mail: info@wadisafin.com

Web: tires.wadisafin.com



Enjoy the
wonderful journey



企业简介 COMPANY PROFILE

东营冠轮车轮有限公司，成立于2016年，是一家专业生产无内胎 及有内胎汽车车轮的大型企业。位于沿海石油之城山东省东营市，地理位置优越，交通运输便利。 公司通过ISO/16949国际质量体系认证，欧洲TUV认证，巴西 INMETRO 认证及美国 DOT 产品注册，为产品质量提供了有力保证。

现有冠轮，顶轮等品牌。产品畅销国内外，已经出口几十个国家地区。主要产品为钢铁制无内胎卡车车轮，钢铁制有内胎卡车车轮，产品全部选用高强度车轮钢制造，实现了车轮的轻量化，高强度，高负载，低成本，达到世界先进水平。 东营冠轮车轮有限公司有着丰富的出口经验，贴心快速定制化的服务，帮助客户发展业务。

Dongying Top Wheel Co., Ltd., established in 2016, is a large-scale enterprise specializing in the production of tubeless and tube automobile wheels. Located in Dongying City, Shandong Province, the coastal oil city, it has a superior geographical location and convenient transportation.

The company has passed ISO/16949 international quality system certification, European TUV certification, Brazil INMETRO certification and American DOT product registration, which provides a strong guarantee for product quality. Existing brands such as Guanlun, Top Wheel and so on. The products sell well at home and abroad, and have been exported to dozens of countries and regions in abroad.

The main products are steel tubeless truck wheels and steel tube truck wheels. All products are made of high-strength wheel steel, which realizes the lightweight, high-strength, high-load, and low cost of the wheels, reaching the world's advanced level.

Dongying Top Wheel Co., Ltd. has a wealth of export experience, caring, fast and customized services to help customers develop their business.



技术参数 TECHNICAL DATA

无内胎系列 TUBELESS WHEEL



17.5X6.00 SERIES 500PCS-20GP 990PCS-40GP 1100PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
17.5X6.00	5	29	JSR22	203.2	146	128	V3-20-4	5	10	1850	8R17.5
	5	32	JSR22	208	150	120/125	V3-20-4	5	12	1850	8.5R17.5
	6	21	H1	205	161	125	V3-20-4	5	12	1850	9R17.5
	6	32	JSR22	222.25	164	127/135	V3-20-4	5	10	1850	9.5R17.5
	6	20.5	JSR22	190	140	128	V3-20-4	5	10	1850	205/65R17.5
	8	21.5/27	JSR18	275	221	135	V3-20-4	5	12	1850	205/75R17.5
	8	24	H1	275	221	134	V3-20-4	5	10	1850	215/75R17.5
	10	26	H1	225	176	135/124	V3-20-4	5	10	1850	225/70R17.5

17.5X6.75 SERIES 450PCS-20GP 990PCS-40GP 1100PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
17.5X6.75	6	29	JSR22	205	161	138	V3-20-4	6	12	1360	8R17.5
	6	32	JSR22	222.25	164	140/145	V3-20-4	6	12	1360	8.5R17.5
	6	21	H1	205	161	131	V3-20-4	6	12	1360	9R17.5
	8	26	H1	275	221	143	V3-20-4	6	12	1360	9.5R17.5
	10	26	H1	225	176	144/153	V3-20-4	6	12	1360	10R17.5

19.5X6.00 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
19.5X6.00	6	21	H1	205	161	127	V3-20-4	5	12	1600	8R19.5
	6	32	JSR22	222.25	163	135	V3-20-4	5	12	1600	8R19.5
	8	32	JSR22	275	214	123/135	V3-20-4	5	12	1600	8R19.5

技术参数

TECHNICAL DATA

无内胎系列 TUBELESS WHEEL

19.5X6.75 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
19.5X6.75	6	32	JSR22	222.25	163	140	V3-20-4	6	12	2500	9.5R19.5
	8	32	JSR22	275	214	136	V3-20-4	6	12	2500	245/70R19.5
	8	26	H1	275	221	140	V3-20-4	6	12	2500	265/70R19.5
	8	32	JSR22	285	221	144	V3-20-4	6	12	2500	265/70R19.5
	10	26	H1	225	176	135	V3-20-4	6	12	2500	265/70R19.5

19.5X7.5 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
19.5X7.5	6	32	JSR22	222.25	164	147	V3-20-4	7	12	2900	245/70R19.5
	8	26	H1	275	221	140	V3-20-4	7	12	2900	265/70R19.5
	8	32	JSR22	275	214	145	V3-20-4	7	12	2900	285/70R19.5
	8	26	H1	275	221	151/155	V3-20-4	7	12	2900	285/70R19.5
	10	26	H1	225	176	151	V3-20-4	7	12	2900	285/70R19.5

22.5X6.00 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X6.00	10	26	H1	225	176	135	V3-20-4	5	14		85R22.5
	8	32	JSR22	275	214	135	V3-20-4	5	14		85R22.5

22.5X6.75 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X6.75	6	32	JSR22	222.25	164	140	V3-20-4	6	14	2800	8R22.5
	8	32	JSR22	285	221	140	V3-20-4	6	14	2800	9R22.5
	8	32	JSR22	275	214	144	V3-20-4	6	14	2800	10R22.5
	10	26	H1	335	281	144/155	V3-20-4	6	14	2800	255/70R22.5
	10	26	H1	225	176	140	V3-20-4	6	14	2800	255/70R22.5

22.5X7.5 SERIES 320PCS-20GP 640PCS-40GP 640PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		W HEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X7.5	demountable					115	V3-20-4			3250	10R22.5
	8	32	JSR22	275	214	165	V3-20-4	7	14	3250	11R22.5
	8	24	H1	275	221	152	V3-20-4	7	14	3250	255/70R22.5
	8	32	JSR22	285	221	150/165	V3-20-4	7	14	3250	265/60R22.5
	10	26	H1	335	281	155/165	V3-20-4	7	14	3250	275/70R22.5
	10	26	H1	285.75	220	152	V3-20-4	7	14	3250	275/80R22.5
	10	32	JSR22	285.75	222	152	V3-20-4	7	14	3250	275/80R22.5

22.5X8.25 SERIES 280PCS-20GP 560PCS-40GP 640PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X8.25	8	32	JSR22	285	221	168	V3-20-6	7	14	3550	11R22.5
	8	32	JSR22	275	214	168	V3-20-6	7	14	3550	12R22.5
	10	26	H1	285.75	220	170/175	V3-20-6	7	14	3550	255/70R22.5
	10	26	H1	285.75	220	168	V3-20-6	6	11	3550	265/60R22.5
	10	32	JSR22	285.75	222	170	V3-20-6	7	14	3550	275/70R22.5
	10	26	H1	335	281	165/171	V3-20-6	7	14	3550	275/80R22.5
	10	26	H1	335	281	120	V3-20-6	7	14	3550	285/60R22.5
	10	26	H1	335	281	0	V3-20-6	7	14	3550	295/80R22.5
	10	26	H1	335	281	169	V3-20-6	7	14	3550	305/70R22.5
	10	27	JSR18	335	281	169	V3-20-6	7	14	3550	305/70R22.5
	10	26	H1	285.75	220	168	V3-20-6	7	14	3550	305/70R22.5
	10	32	JSR22	285.75	220	168	V3-20-6	7	14	3550	305/70R22.5
	demountable					120	V3-20-6			3550	305/70R22.5

技术参数 TECHNICAL DATA

无内胎系列 TUBELESS WHEEL



22.5X9.0 SERIES 280PCS-20GP 560PCS-40GP 640PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X9.0	8	26	H1	275	221	175	V3-20-6	7	14	4000	12R22.5
	8	32	JSR22	285	221	175	V3-20-6	7	14	4000	285/60R22.5
	10	26	H1	285.75	220	175	V3-20-6	7	14	4000	295/60R22.5
	10	32	JSR22	285.75	222	175	V3-20-6	7	14/16	4000	295/80R22.5
	10	26	H1	335	281	175	V3-20-6	7	14	4000	305/60R22.5
	10	26	H1	335	281	175	V3-20-6	6	11	4000	305/70R22.5
	10	26	H1	335	281	170	V3-20-6	7	14	4000	315/60R22.5
	10	26	H1	335	281	0	V3-20-6	7	14	4000	315/70R22.5
	10	26	H1	335	281	120	V3-20-6	7	14	4000	315/75R22.5
	demountable					130	V3-20-6			4000	315/80R22.5
	demountable					122	V3-20-6			4000	315/80R22.5

22.5X9.75 SERIES 280PCS-20GP 560PCS-40GP 600PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X9.75	10	26	H1	285.75	220	180	V3-20-6	7	14	4000	13R22.5
	10	26	H1	335	281	180	V3-20-6	7	14	4000	13R22.5

24.5X8.25 SERIES 210PCS-20GP 420PCS-40GP 480PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
24.5X8.25	10	26	H1	285.75	220	168	V3-20-6	7	12	3550	11R24.5
	10	26	H1	335	281	170	V3-20-6	7	16	3550	11R24.5
	10	32	JSR22	285.75	222	168	V3-20-6	7	16	3550	11R24.5

24.5X9.0 SERIES 208PCS-20GP 416PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
24.5X9.0	10	26	H1	335	281	175	V3-20-6	7	16	3750	12R24.5
	demountable					127	V3-20-6			3750	12R24.5

22.5X11.75 SERIES 240PCS-20GP 480PCS-40GP 480PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X11.75	8	24	H1	275	221	0	T R570	7	12	4500	355/50R22.5
	10	26	H1	335	281	120	T R570	7	14	4500	365/70R22.5
	10	26	H1	335	281	120	T R570	6	12	4500	375/90R22.5
	10	26	H1	335	281	0	T R570	7	12	4500	385/55R22.5
	10	26	H1	335	281	120	T R570	7	14	4500	385/65R22.5
	10	26	H1	335	281	0	T R570	7	12	4500	385/65R22.5
	10	26	H1	335	281	135	T R570	7	14	4500	385/65R22.5
	10	26	H1	335	281	98	T R570	7	14	4500	385/65R22.5

22.5X13.00 SERIES 240PCS-20GP 480PCS-40GP 480PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	RECOM MEND VALVE	T HICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X13.00	10	26	H1	335	281	0	T	7	14	5300	415/45R22.5
	10	26	H1	285.75	220	0	R570	7	14	5300	425/65R22.5
											445/65R22.5

T
R570



技术参数 TECHNICAL DATA

有内胎系列 TUBE TYPE WHEEL

5.50F-16 SERIES 840PCS-20GP

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
16-5.50F	5	32	JSR22	208	150	125	10	1220	7.00R16
	5	29	JSR22	203.2	146	115	10	1220	7.50R16
	5	32	JSR22	208	150	115	10	1220	7.50R16
	6	20.5	JSR22	190	140	110	10	1220	7.50R16
	6	32	JSR22	222.25	164	115	10	1220	7.50R16
	6	32	JSR22	222.25	164	115	10	1220	7.50R16

6.00G-16 SERIES 760PCS-20GP

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
6.00G-16	5	32	JSR22	203.2	146	127	10	1400	8.25R16
	5	32	JSR22	208	150	127	12	1400	8.25R16
	5	32	JSR22	208	150	136	10	1400	8.25R16
	6	20.5	JSR22	190	140	125	10	1400	8.25R16
	6	32	JSR22	222.25	163	125	10	1400	8.25R16
	6	32	JSR22	222.25	164	135/141	10	1400	8.25R16
	6	32	JSR22	222.25	164	135/141	10	1400	8.25R16

6.50-16 SERIES 780PCS-20GP

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
6.50-16	6	32	JSR22	222.25	163	135	10	1400	7.50R16
	8	24	H1	222.25	164	135	10	1400	8.25R16



技术参数 TECHNICAL DATA



有内胎系列 TUBE TYPE WHEEL

7.5V-20 SERIES 360PCS-20GP 560PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	DISC T HICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
7.5V-20	8	32	JSR22	285	221	165	14	3730	10.00R20
	10	32	JSR22	285.75	222	170	14	3730	10.00R20
	10	26	H1	335	281	165	14	3730	10.00R20
	10	26	H1	285.75	220	165	14	3730	10.00R20

8.00V-20 SERIES 320PCS-20GP 520PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	DISC T HICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
8.00V-20	8	32	JSR22	275	214	173	16	3270	11.00R20
	10	26	H1	335	281	175	16	3270	11.00R20
	10	32	JSR22	285.75	222	175	14	3270	11.00R20
	10	26	H1	285.75	220	173	16	3270	11.00R20

8.50-20 SERIES 360PCS-20GP 560PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	DISC T HICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
8.50-20	8	32	JSR22	285	221	175	14	3730	1200R20
	10	26	H1	335	281	180	14	3730	1200R20
	10	32	JSR22	285.75	221	175	14	3730	1200R20
	10	26	H1	285.75	220	180	16	3730	1200R20

8.50-24 SERIES 208PCS-20GP 370PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENT ER HOLE	OFFSET	DISC T HICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
8.50-24	10	27	JSR18	335	281	180	14/16	4500	1200R24
	10	26	H1	335	281	180	14/16	4500	1200R24





Address: Erbil, Southern Industry

TEL: +964 770 445 4256

E-mail: info@wadisafin.com

Web: tires.wadisafin.com